





# QT 80 - 40

## Thru-Hull - Led serviced From inside

### Mounting

Hull Material	GRP / Fiberglass
Boat size	Up to 30meters (90 ft)
Spacing	1 - 3m (2' - 4ft)
Beam Angle	68°
Installation Angles	Flush

### Technical

Lumens	6,000
Kelvin	6,500
Typical LED Life Expectancy	20,000 hrs
Min-Max Operating Voltage	11 - 28V DC
Current / Amp draw	4.0 - 1.8 amps
Driver Type	Integral
Driver Protection	Reverse Polarity Thermal Protected
Control Options	On / Off Switch
Bonding	Securing Ring

### Physical

Hole Cut-out	61mm (2.5")
Length of fixture	108mm (4.25")
Diameter of fixture	82mm (3.22")
Profile (height) of fixture	4mm (3/16")
Removal Space Required	160mm (6.5")
Total weight	1kg (2.2 lb)
Cable Length	2meters (10ft)
Max Hull thickness	62mm (2.5")
Material	Armor Coated AB2 Bronze
Growth Resistant Lens	Borosilicate Glass

### Color

White



### Part Number

QT- 80- 40W

Blue



N/A

RGB+W



N/A



Your Local Dealer



© 2015 Underwater Lights Limited All Rights Reserved.  
Underwater lights limited reserves the right to change specifications without notice.

The Great Dunton Forge, London Road  
Dunton Green, Sevenoaks, Kent TN13 2TD UK  
T: +44 (0) 1732 455753 • F: +44 (0) 1732 743233  
E: uwl@underwaterlights.com  
[www.underwaterlights.com](http://www.underwaterlights.com)

VAT NO: 556 4425 31

Registered in England No: 2348038



