

PRODUCT GUIDE

For Marine Generators

AMP

A SAIM Group Company

Atlantis Marine Power Limited
www.atlantismarine.com
sales@atlantismarine.com
+44 (0)1752 208810



KOHLER®

IN POWER. SINCE 1920.

ALWAYS PRESENT NEVER NOTICED



KOHLER® marine generators are smaller. Quieter. With less vibration.* Each one is built to last and designed to go unnoticed.

Enjoy the journey.

*Compared to previous KOHLER generator models.





WHY KOHLER

PROVEN RELIABILITY

Every KOHLER generator is extensively quality-tested—before model release and before leaving the factory. The result is proven reliability.

PREMIUM LIMITED WARRANTY

Enjoy full protection throughout the duration of our industry-leading warranty.

GLOBAL SUPPORT

With nearly 1000 sales and service locations around the world, we're everywhere you go.

Information, specifications, materials and dimensions are subject to change without notice.



DIESEL GENERATORS

Equipped with either an Advanced Digital Control IId (5 to 11-kW units) or Decision-Maker® Controller (12 to 200 kW) and the industry's most acoustically advanced sound shields, KOHLER® diesel generators provide the ultimate in overall performance.

Standard Features

- Remote start connection availability
- Class H insulation
- Multivoltage adjustability
- Voltage regulation of $\pm 1-2\%$
- Frequency regulation $\pm 5\%$ droop, .8% steady state for mechanically governed models, .5% isochronous for electronically governed models
- Radio suppression

Optional Accessories

- Remote start and meter panel kit
- Siphon break
- Remote digital gauge
- Sound shield (depending on model)

*55-kW generator with
DEC 3500 Controller*



Information, specifications, materials and dimensions are subject to change without notice.

DIESEL GENERATORS

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)
6EKOD	6	60	3	1800	1	120	50	H – 780 (30.7) x 528 (20.8) x 559 (22) U – 743 (29.3) x 448 (17.6) x 536 (21.1)	H – 222 (489) U – 185 (407)
5EFKOD	5	50		1500		120 / 240	50 / 25		
						115 / 230	43.4 / 21.7		
						230	21.7		
						240	20.8		
9EKOZD	8.5	60	3	1800	1	120	70.8	H – 865 (34.1) x 528 (20.8) x 559 (22) U – 827 (32.6) x 448 (17.6) x 536 (21.1)	H – 249 (548) U – 211 (465)
7EFKOZD	7	50		1500		120 / 240	70.8 / 35.4		
						115 / 230	60.8 / 30.4		
						230	30.4		
						240	29.2		
11EKOZD	11	60	4	1800	1	120	91.7	H – 960 (37.8) x 528 (20.8) x 559 (22) U – 922 (36.3) x 448 (17.6) x 536 (21.1)	H – 279 (616) U – 241 (532)
9EFKOZD	9	50		1500		120 / 240	91.7 / 45.8		
						115 / 230	78.3 / 39.1		
						230	39.1		
						240	37.5		
11EKOZD	11	60	4	1800	3	220 / 380	20.9	H – 960 (37.8) x 528 (20.8) x 559 (22) U – 922 (36.3) x 448 (17.6) x 536 (21.1)	H – 406 (896) U – 376 (830)
9EFKOZD	9	50		1500		240 / 416	19.1		
						120 / 240	33.1		
						127 / 220	36.1		
						230 / 400	16.2		
14EKOZD	14	60	3	1800	1	120	117	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 984 (38.8) x 580 (22.8) x 695 (27.4)	H – 395 (870) U – 376 (830)
12EFKOZD	12	50		1500		120 / 240	59		
						230	53		
						240	40		

*kW rating varies by voltage. Consult the generator spec sheet for more detail.

Information, specifications, materials and dimensions are subject to change without notice.

DIESEL GENERATORS

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)
14EKOZD	14	60	3	1800	3	120 / 208	49	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 984 (38.8) x 580 (22.8) x 695 (27.4)	H – 406 (896) U – 376 (830)
						120 / 240	43		
					1	120 / 240	59		
						127 / 220	46		
						3	139 / 240		
277 / 480	22								
12EFKOZD	12	50		1500	3	110 / 190	46		
						115 / 230	38		
					3	115 / 230	53		
						120 / 208	42		
						230 / 400	22		
						240 / 416	21		
						220 / 380	23		
			120			134			
16EKOZD	16	60	3	1800	1	120 / 240	67	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 1003 (39.5) x 580 (22.8) x 695 (27.4)	H – 406 (896) U – 376 (830)
13.5EFKOZD	14	50		1500		230	59		
						240	40		
						16EKOZD	16		
120 / 240	49								
1	120 / 240	67							
	127 / 220	53							
	3	139 / 240	49						
277 / 480		25							
13.5EFKOZD	13.5	50	1500	3	110 / 190	52			
					115 / 230	43			
					115 / 230	59			
				3	120 / 208	47			
					230 / 400	25			
					240 / 416	24			
					220 / 380	26			

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)
21EKOZD	21 / 21	60	4	1800	1	120	175	H – 1197 (47.12) x 652.5 (25.69) x 711(27.99) U – 1121 (44.13) x 577.5 (22.74) x 694(27.31)	H – 480 (1059) U – 440 (970)
	21 / 21					120 / 240	88		
18EFKOZD	18 / 18	50		1500		230	79		
	14.5 / 14.5					240	61		
21EKOZD	21	60	4	1800	3	120 / 208	73	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1121 (44.1) x 577.5 (22.7) x 694 (27.3)	H – 480 (1059) U – 440 (970)
						120 / 240	64		
					1	120 / 240	80		
						127 / 220	69		
					3	139 / 240	64		
						277 / 480	32		
17EFKOZD	17	50		1500	3	110 / 190	65		
						115 / 230	54		
					1	115 / 230	70		
						3	120 / 208		
					230 / 400		31		
					240 / 416		29		
					220 / 380		33		
					24EKOZD	24	60		
120 / 240	100								
20.5EFKOZD	21	50	1500	230	90				
				240	78				

*kW rating varies by voltage. Consult the generator spec sheet for more detail.
Information, specifications, materials and dimensions are subject to change without notice.

DIESEL GENERATORS

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)
24EKOZD	24	60	4	1800	3	120 / 208	84	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1138 (44.8) x 577.5 (22.7) x 694 (27.3)	H – 489 (1078) U – 449 (990)
						120 / 240	73		
					1	120 / 240	92		
						127 / 220	79		
					3	139 / 240	73		
						277 / 480	37		
20.5EFKOZD	20.5	50		1500	3	110 / 190	78		
						115 / 230	65		
					1	115 / 230	85		
						120 / 208	72		
					3	230 / 400	37		
						240 / 416	36		
						220 / 380	39		
			32EKOZD			32	60	4	1800
32	120 / 208	111							
32	3	120 / 240		96					
31		120 / 240		142					
32	3	127 / 220		105					
32		139 / 240		96					
32		277 / 480		48					
28EFKOZD	28	50		1500	1	230			
	23		240			96			
	28		3		110 / 190	106			
	28				110 / 220	92			
	27		1		115 / 230	117			
	28				120 / 208	97			
	28		3		230 / 400	51			
	28				240 / 416	49			
	28				220 / 380	53			

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused / R – Radiator	Weight (Wet) kg (lb)
40EKOZD	40	60	4	1800	1	120 / 240	152	H – 1354 (53.31) x 661 (26.04) x 778 (30.64) U – 1274 (50.17) x 643 (25.33) x 733 (28.86)	H – 637 (1404) U – 567 (1250)
	40				3	120 / 208	139		
	40					120 / 240	120		
	34				1	120 / 240	142		
	40				3	127 / 220	131		
	40					139 / 240	120		
	40					277 / 480	60		
35EFKOZD	35	50		1500	1	230	152		
	32					240	133		
	34				3	110 / 190	129		
	34					110 / 220	112		
	30				1	115 / 230	130		
	35				3	120 / 208	121		
	35					230 / 400	63		
	35					240 / 416	61		
	34					220 / 380	65		
33EFOZDJ	33	50	4	1500	3	110 / 190	125		
						110 / 220	108		
					1	115 / 230	143		
						220 / 380	63		
					3	230 / 400	60		
						240 / 416	57		

*kW rating varies by voltage. Consult the generator spec sheet for more detail.
Information, specifications, materials and dimensions are subject to change without notice.

DIESEL GENERATORS

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused / R – Radiator	Weight (Wet) kg (lb)
40EFOZDJ	40	50	4	1500	3	110 / 190	152	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1080 (2380) U – 971 (2140) R – 993 (2190)*
						110 / 220	131		
					1	115 / 230	174		
					3	220 / 380	76		
						230 / 400	72		
50EFOZDJ	50	50	4	1500	3	110 / 190	190	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1114 (2456) U – 1005 (2216) R – 1028 (2266)*
						110 / 220	164		
					1	115 / 230	196		
					3	220 / 380	95		
						230 / 400	90		
55EOZDJ	55	60	4	1800	3	120 / 208	191	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*
						120 / 240	165		
					1	120 / 240	221		
					3	127 / 220	180		
						139 / 240	165		
45EFOZDJ	45	50	4	1500	3	277 / 480	83	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*
						110 / 190	171		
					1	110 / 220	148		
						115 / 230	196		
					3	220 / 380	86		
						230 / 400	79		
45EFOZDJ	45	50	4	1500	3	240 / 416	71	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*
						240 / 416	71		

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused / R – Radiator	Weight (Wet) kg (lb)
65EOZDJ	65	60	4	1800	3	120 / 208	226	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1125 (2480) U – 1016 (2240) R – 1039 (2290)*
						120 / 240	195		
					1	120 / 240	221		
					3	127 / 220	213		
						139 / 240	195		
						277 / 480	98		
55EFOZDJ	55	50		1500	3	110 / 190	209		
						110 / 220	181		
					1	115 / 230	217		
					3	220 / 380	105		
						230 / 400	95		
						240 / 416	89		
80EOZDJ	80	60	4	1800	3	120 / 208	278	H – 1754 (69) x 831 (32.7) x 1032 (40.6) U – 1657 (65.2) x 753 (29.6) x 999 (39.3) R – 1992 (78.4) x 890 (35) x 1277 (50.2)	H – 1270 (2800) U – 1148 (2530) R – 1179 (2600)*
						120 / 240	241		
						127 / 220	262		
						139 / 240	241		
						277 / 480	120		
						110 / 190	266		
70EFOZDJ	70	50		1500		110 / 220	230		
						220 / 380	133		
						230 / 400	126		
						240 / 416	121		

*kW rating varies by voltage and radiator models. Consult the generator spec sheet for more detail.

Information, specifications, materials and dimensions are subject to change without notice.

DIESEL GENERATORS

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused / R – Radiator	Weight (Wet) kg (lb)
99EOZDJ	99	60	4	1800	3	120 / 208	343	H – 1829 (72) x 831 (32.7) x 1032 (40.6) U – 1732 (68.2) x 753 (29.6) x 999 (39.3) R – 2067 (81.3) x 890 (35) x 1277 (50.2)	H – 1356 (2990) U – 1243 (2740) R – 1275 (2810)*
						120 / 240	298		
						127 / 220	325		
						139 / 240	298		
						277 / 480	149		
80EFOZDJ	80	50		1500		110 / 190	304		
						110 / 220	262		
						220 / 380	152		
						230 / 400	144		
						240 / 416	139		
125EOZDJ	125	60		6		1800	3		
			120 / 240		376				
			127 / 220		410				
			139 / 240		376				
			277 / 480		188				
100EFOZDJ	100	50	1500		110 / 190	380			
					120 / 208	347			
					110 / 220	328			
					220 / 380	190			
					230 / 400	180			
						240 / 416	173		

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused / R – Radiator	Weight (Wet) kg (lb)
150EOZDJ	150	60	6	1800	3	120 / 208	520	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2091 (82.3) x 893 (35.2) x 1003 (39.5) R – 2498 (98) x 1129 (44.5) x 1275 (50.2)	H – 1719 (3789) U – 1551 (3419) R – 1613 (3557)
						120 / 240	451		
						127 / 220	492		
						139 / 240	451		
						277 / 480	226		
125EFOZDJ	125	50		1500		110 / 190	474		
						120 / 208	433		
						110 / 220	409		
						220 / 380	237		
						230 / 400	225		
						240 / 416	217		
200EOZDJ	200	60	6	1800	3	120 / 208	694	H – 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U – 2490 (98) x 970 (38.2) x 1086 (42.8)	H – 2147 (4733) U – 2067 (4558)
						120 / 240	601		
						127 / 220	656		
						139 / 240	601		
						277 / 480	301		
175EFOZDJ	175	50		1500		110 / 190	665		
						110 / 220	574		
						120 / 208	607		
						220 / 380	332		
						230 / 400	316		
			240 / 416			304			

*kW rating varies by voltage and radiator models. Consult the generator spec sheet for more detail.
Information, specifications, materials and dimensions are subject to change without notice.





GLOBAL SUPPORT

With nearly 1000 sales and service locations
all over the world, we're everywhere you go.

AMERICAS CARIBBEAN

+1 920 565 3381
+1 800 544 2444
FAX +1 920 459 1646

CHINA

+86 21 26062169
+86 400 1808 900

EUROPE MIDDLE EAST AFRICA

+31 168 331630
FAX +31 168 331631

ASIA PACIFIC

+65 6660 2681
FAX +65 6264 6455

NEW ZEALAND AUSTRALIA

+61 88 29 02100

INDIA

+91 80 42867000
FAX +91 80 23615972



KOHLERPOWER.COM

Printed in U.S.A. G12-480 06/18 © 2018 by Kohler Co.

KOHLER
IN POWER. SINCE 1920.